

CODE REQUIRED SIGNAGE

DESIGN, CONSTRUCTION, INSTALLATION, AND LOCATION OF INTERIOR SIGNAGE AND GRAPHICS SHALL COMPLY WITH THE FLORIDA BUILDING CODE AND THE UNIFORM FIRE SAFETY STANDARDS AS ADOPTED BY THE STATE FIRE MARSHAL AND THE FOLLOWING:

MAXIMUM CAPACITY SIGNS IN EACH SPACE WITH A CAPACITY OF 50 OR MORE OCCUPANTS; THE SIGNS SHALL BE MOUNTED ADJACENT TO THE MAIN ENTRANCE DOOR (SEE PLANS FOR MORE INFORMATION).

ROOM NAME AND ROOM NUMBER SHALL BE PROVIDED FOR EACH SPACE.

A GRAPHIC DIAGRAM OF PRIMARY AND EMERGENCY EVACUATION ROUTES SHALL BE POSTED ADJACENT TO THE PRIMARY EXIT DOOR FROM EACH SPACE OCCUPIED BY SIX OR MORE STUDENTS. THE DIAGRAM SHALL CLEARLY INDICATE, BY CONTRASTING COLOR AND NUMBER, EACH ROUTE OF EVACUATION.

SIGNS NECESSARY TO MEET ACCESSIBILITY REQUIREMENTS SHALL BE PROVIDED (SEE THE ADA SIGNAGE PARAGRAPH).

HAZARDOUS WORK AND STORAGE AREAS SHALL BE IDENTIFIED BY APPROPRIATE CAUTION SIGNS.

BUILDING SIGNAGE, SIGNS WHICH DESIGNATE PERMANENT ROOMS AND SPACES SHALL COMPLY WITH ADA REQUIREMENTS AS SPECIFIED IN THE ADA SIGNAGE PARAGRAPH, OTHER SIGNS WHICH PROVIDE DIRECTION TO, OR INFORMATION ABOUT, FUNCTIONAL SPACES OF THE BUILDING SHALL ALSO COMPLY WITH ADA REQUIREMENTS. BUILDING DIRECTORIES, MENUS, AND ALL OTHER SIGNS WHICH ARE TEMPORARY ARE NOT REQUIRED TO COMPLY WITH ADA REQUIREMENTS.

ADA BUILDING SIGNAGE

ELEMENTS AND SPACES OF ACCESSIBLE FACILITIES WHICH SHALL BE IDENTIFIED BY THE INTERNATIONAL SYMBOL OF ACCESSIBILITY AND WHICH SHALL COMPLY WITH THE ADA SIGNAGE REQUIREMENTS ARE:

(A) PARKING SPACES DESIGNATED AS RESERVED FOR INDIVIDUALS WITH DISABILITIES;

(B) ACCESSIBLE PASSENGER LOADING ZONES;

(C) ACCESSIBLE ENTRANCES WHEN NOT ALL ARE ACCESSIBLE (INACCESSIBLE ENTRANCES SHALL HAVE DIRECTIONAL SIGNAGE TO INDICATE THE ROUTE TO THE NEAREST ACCESSIBLE ENTRANCE);

(D) ACCESSIBLE TOILET AND BATHING FACILITIES WHEN NOT ALL ARE ACCESSIBLE.

APPROPRIATE ACCESSIBLE SIGNAGE INDICATING THE LOCATION OF THE NEAREST ACCESSIBLE ENTRANCE(S) SHALL BE INSTALLED AT OR NEAR THE INACCESSIBLE ENTRANCE, SUCH THAT A PERSON WITH DISABILITIES WILL NOT BE REQUIRED TO RETRACE THE APPROACH ROUTE FROM THE INACCESSIBLE ENTRANCE.

SIGNAGE PROPERTIES

SIGNAGE REQUIRED TO BE ACCESSIBLE SHALL COMPLY WITH THE FOLLOWING APPLICABLE PROVISIONS.

CHARACTER PROPORTION, LETTERS AND NUMBERS ON SIGNS SHALL HAVE A WIDTH-TO-HEIGHT RATIO BETWEEN 3:5 AND 1:1 AND A STROKE WIDTH-TO-HEIGHT RATIO BETWEEN 1:3 AND 1:10.

CHARACTER HEIGHT, CHARACTERS AND NUMBERS ON SIGNS SHALL BE SIZED ACCORDING TO THE VIEWING DISTANCE FROM WHICH THEY ARE TO BE READ. THE MINIMUM HEIGHT IS MEASURED USING AN UPPER CASE "X". LOWER CASE CHARACTERS ARE PERMITTED. CHARACTERS 80" ABOVE FINISHED FLOOR SHALL BE 3" MINIMUM HEIGHT.

RAISED AND BRAILLED CHARACTERS AND PICTORIAL SYMBOL SIGNS (PICTOGRAMS), LETTERS AND NUMERALS SHALL BE RAISED 1/32 INCHES, UPPER CASE. SANS SERIF OR SIMPLE SERIF TYPE AND SHALL BE ACCOMPANIED WITH GRADE 2 BRAILLE. RAISED CHARACTERS SHALL BE AT LEAST 5/8 INCHES HIGH, BUT NO HIGHER THAN 2 INCHES. PICTOGRAMS SHALL BE ACCOMPANIED BY THE EQUIVALENT VERBAL DESCRIPTION PLACED DIRECTLY BELOW THE PICTOGRAM. THE BORDER DIMENSION OF THE PICTOGRAM SHALL BE 6 INCHES MINIMUM IN HEIGHT.

FINISH AND CONTRAST: THE CHARACTERS AND BACKGROUND OF SIGNS SHALL BE EGGSHELL, WHITE, OR OTHER NON-GLOSS FINISH. CHARACTERS AND SYMBOLS SHALL CONTRAST WITH THEIR BACKGROUND EITHER LIGHT CHARACTERS ON A DARK BACKGROUND OR DARK CHARACTERS ON A LIGHT BACKGROUND.

MOUNTING LOCATION AND HEIGHT: WHERE PERMANENT IDENTIFICATION IS PROVIDED FOR ROOMS AND SPACES, SIGNS SHALL BE INSTALLED ON THE WALL ADJACENT TO THE LATCH SIDE OF THE DOOR, WHERE THERE IS NO WALL SPACE TO THE LATCH SIDE OF THE DOOR, INCLUDING AT DOUBLE LEAF DOORS, SIGNS SHALL BE PLACED ON THE NEAREST ADJACENT WALL. MOUNTING HEIGHT SHALL BE 60 INCHES ABOVE THE FINISH FLOOR TO THE CENTERLINE OF THE SIGN. MOUNTING LOCATION FOR SUCH SIGNAGE SHALL BE SO THAT A PERSON MAY APPROACH WITHIN 3 INCHES OF SIGNAGE WITHOUT ENCOUNTERING PROTRUDING OBJECTS OR STANDING WITHIN THE SWING OF A DOOR.

SYMBOLS OF ACCESSIBILITY.

(1) FACILITIES AND ELEMENTS REQUIRED TO BE IDENTIFIED AS ACCESSIBLE SHALL USE THE INTERNATIONAL SYMBOL OF ACCESSIBILITY. SEE SYMBOLS BELOW.

(2) VOLUME CONTROL TELEPHONES, TELEPHONES REQUIRED TO HAVE A VOLUME CONTROL SHALL BE IDENTIFIED BY A SIGN CONTAINING A DEPICTION OF A TELEPHONE HANDSET WITH ROTATING SOUND WAVES.

(3) TEXT TELEPHONES, TEXT TELEPHONES SHALL BE IDENTIFIED BY THE INTERNATIONAL TDD SYMBOL. IN ADDITION, IF A FACILITY HAS A PUBLIC TEXT TELEPHONE, DIRECTIONAL SIGNAGE INDICATING THE LOCATION OF THE NEAREST TEXT TELEPHONE SHALL BE PLACED ADJACENT TO ALL BANKS OF TELEPHONES WHICH DO NOT CONTAIN A TEXT TELEPHONE. SUCH DIRECTIONAL SIGNAGE SHALL INCLUDE THE INTERNATIONAL TDD SYMBOL. IF A FACILITY HAS NO BANKS OF TELEPHONES, THE DIRECTIONAL SIGNAGE SHALL BE PROVIDED AT THE ENTRANCE (E.G., IN A BUILDING DIRECTORY).

(4) ASSISTIVE LISTENING SYSTEMS, IN ASSEMBLY AREAS WHERE PERMANENTLY INSTALLED ASSISTIVE LISTENING SYSTEMS ARE REQUIRED BY SECTION 114.1.1(9)(B) THE AVAILABILITY OF SUCH SYSTEMS SHALL BE IDENTIFIED WITH SIGNAGE THAT INCLUDES THE INTERNATIONAL SYMBOL OF ACCESS FOR HEARING LOSS.

EXIT SIGNS

EXITS SHALL BE MARKED BY AN APPROVED SIGN READY VISIBLE FROM ANY DIRECTION OF EXIT ACCESS. EVERY EXIT SIGN SHALL BE SUTARLY ILLUMINATED BY A RELIABLE LIGHT SOURCE, EXTERNALLY AND INTERNALLY ILLUMINATED SIGNS SHALL BE VISIBLE IN BOTH NORMAL AND EMERGENCY LIGHTING. NEW SIGN PLACEMENT SHALL BE SUCH THAT NO POINT IN AN EXIT ACCESS CORRIDOR IS IN EXCESS OF THE RATED VIEWING DISTANCE OR 100 FEET WHICHEVER IS LESS, FROM THE NEAREST SIGN.

EVERY REQUIRED SIGN SHALL BE LOCATED AND OF SUCH SIZE, DISTINCTIVE COLOR AND DESIGN AS TO BE READILY VISIBLE AND SHALL PROVIDE CONTRAST WITH INTERIOR FINISH OR OTHER SIGNS. NO EQUIPMENT THAT IMPAIRS VISIBILITY OF AN EXIT SIGN SHALL BE PERMITTED, NOR SHALL THERE BE ANY BRIGHTLY ILLUMINATED SIGN OR OBJECT IN OR NEAR THE LINE OF VISION OF THE REQUIRED EXIT SIGN OF SUCH A CHARACTER AS TO DETRACT ATTENTION FROM THE EXIT SIGN. FLOOR PROXIMITY SIGNS, WHERE REQUIRED, SHALL BE IN ACCORDANCE WITH THE FBG.

EXIT STAR DOOR OR TACTILE SIGNAGE: TACTILE SIGNAGE STAINING-"EXIT" AND COMPLYING WITH ICC/ANSI A117.1 SHALL BE INSTALLED ADJACENT TO THE LATCH SIDE OF THE DOOR 60 INCHES ABOVE THE FINISHED FLOOR TO THE CENTER LINE OF THE SIGN.

WHERE THE DIRECTION OF TRAVEL TO REACH THE NEAREST EXIT IS NOT APPARENT, A DIRECTIONAL SIGN READING "EXIT" OR A SIMILAR DESIGNATION WITH A DIRECTIONAL INDICATION SHOWING THE DIRECTION OF TRAVEL SHALL BE PLACED IN EVERY LOCATION. DIRECTIONAL SIGNS SHALL BE LISTED.

STAR IDENTIFICATION: AN APPROVED SIGN SHALL BE LOCATED AT EACH FLOOR LEVEL LANDING IN ALL ENCLOSED STAIRWAYS OF BUILDINGS FOUR OR MORE STOREYS IN HEIGHT. THE SIGN SHALL INDICATE THE FLOOR LEVEL AND THE AVAILABILITY OF ROOF ACCESS FROM THAT STAIRWAY AND AN IDENTIFICATION OF THE STAIRWAY. THE SIGN SHALL ALSO STATE THE FLOOR LEVEL OF AND DIRECTION TO EXIT DISCHARGE. THE SIGN SHALL BE LOCATED APPROXIMATELY 5 FEET ABOVE THE FLOOR LANDING IN A POSITION WHICH IS READILY VISIBLE WHEN THE DOOR IS IN THE OPEN OR CLOSED POSITION. THE FLOOR LEVEL DESIGNATION SHALL ALSO BE TACTILE IN ACCORDANCE WITH ADA REQUIREMENTS.

STAIRWAY FLOOR NUMBER SIGNS: A SIGN SHALL BE PROVIDED AT EACH FLOOR LANDING IN INTERIOR EXIT ENCLOSURES CONNECTING MORE THAN THREE STOREYS DESIGNATING THE FLOOR LEVEL. THE TERMINUS OF THE TOP AND BOTTOM OF THE STAIR ENCLOSEURE AND THE IDENTIFICATION OF THE STAIR. THE SIGNAGE SHALL ALSO STATE THE STORY OF, AND THE DIRECTION TO THE EXIT DISCHARGE AND THE AVAILABILITY OF ROOF ACCESS FROM THE STAIRWAY FOR THE FIRE DEPARTMENT. THE SIGN SHALL BE LOCATED 5 FEET ABOVE THE FLOOR LANDING IN A POSITION THAT IS READILY VISIBLE WHEN THE DOORS ARE IN THE OPEN AND CLOSED POSITIONS.

TOILET FACILITIES

RESTROOMS SHALL BE DESIGNATED BY A LEGIBLE SIGN FOR EACH SEX OR FOR UNISEX FACILITIES. SIGNS SHALL BE READILY VISIBLE AND LOCATED NEAR THE ENTRANCE TO EACH TOILET FACILITY.

3

ROOM FINISH SCHEDULE

ROOM NAME	FLOOR		WALLS				CEILING	REMARKS		
	MATL.	FIN.	TEXTURE	FIN.	TEXTURE	FIN.			TEXTURE	FIN.
LOBBY	VCT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	EXP-1
GRINA ROOM	OPT-1	FB-1	GB	P-3	GB	P-3	GB	P-3	GB	CLG-1
VESTIBULE	VCT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	CLG-2
NAVE	VCT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	EXP-1
CHOIR AREA	OPT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	EXP-1
BAUD AREA	OPT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	EXP-1
PIANO AREA	OPT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	EXP-1
MENS TOILETS	PC-3	FB-1	GBM	P-1	GBM	P-1	GBM	P-1	GBM	WALL TILE 48" A.F.F.
PC-4	GBM									
PC-2	GBM									
PC-4	GBM									WALL TILE 48" A.F.F.
WOMENS TOILETS	PC-4	FB-1	GBM	P-1	GBM	P-1	GBM	P-1	GBM	
PC-4	GBM									
OFFICES	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
CLASSROOMS	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
MEN CHANGING ROOM	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
WOMEN CHANGING ROOM	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
A/V ROOM	OPT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
MECHANICAL ROOM	PC-1	FB-2	GB	P-3	GB	P-3	GB	P-3	GB	
STORAGE	PC-1	FB-2	GB	P-3	GB	P-3	GB	P-3	GB	
ADMINISTRATION	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
PASTOR'S OFFICE	VCT-1	FB-1	GB	P-2	GB	P-2	GB	P-2	GB	
HALL	VCT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	
KITCHEN	PC-1	FB-2	FR-1	FR-1		FR-1		FR-1		
STAR WATYS	VCT-1	FB-1	GB	P-3	GB	P-3	GB	P-3	GB	CLG-2
ELECTRIC ROOM	PC-1	FB-2	GB	P-3	GB	P-3	GB	P-3	GB	EXP-2
CORRIDOR	VCT-1	FB-1	GB	P-1	GB	P-1	GB	P-1	GB	ACF-1
										CLG-2

NOTES:

WALL AND FINISH MATERIALS SHALL NOT EXCEED THE FLAME SPREAD CLASSIFICATION AS INDICATED ON QN-1 FINISH NOTE 1.

ELEVATION CHANGE BETWEEN ADJACENT SPACES WITH DIFFERENT FLOOR FINISHES SHALL NOT EXCEED 1/2". PROVIDE TAPERING MATERIAL AS REQUIRED TO LEVEL TRANSITION

ALL PORCELAIN, QUARRY, CERAMIC OR STONE TILE SHALL BE INSTALLED AS RECOMMENDED BY THE TILE COUNCIL OF AMERICA. SUBMIT INSTALLATION METHOD TO ARCHITECT FOR APPROVAL.

GYPNUM BOARD FINISH:

ALL ROOMS RECEIVING SEMI-GLOSS OR SATIN PAINT SHALL RECEIVE A LEVEL 5 GYPNUM BOARD FINISH.

ALL ROOMS RECEIVING FLAT PAINT SHALL RECEIVE LEVEL 4 GYPNUM BOARD FINISH.

GYPNUM BOARD FINISHES ACCORDING TO THE GYPNUM ASSOCIATION RECOMMENDATIONS.

ABBREVIATIONS

AP	ACOUSTICAL CEILING PANELS
CMU	CONCRETE MASONRY UNITS
CONC.	CONCRETE
CLG.	CEILING
OPT	CARPET
G-	GLASS
FB-	FLOOR BASE
FF	FACTORY FINISH
GB	GYPNUM BOARD
GBM	GYPNUM BOARD MOISTURE RESISTANT
M-	MULLIONS
NF	NO FINISH
P-	PAINT
PC-	PORCELAIN/ CERAMIC TILE
WT	WALL TILE
VCT	VINYL COMPOSITE TILE
EXP	EXPOSED
FRP	FIRE REINFORCE PLASTIC

FINISH LEGEND

FINISH	FLOORS	WALLS	CEILING	REMARKS
P-1	SHERWIN WILLIAMS SATIN	P-1	SHERRIN WILLIAMS SATIN	ACOUSTICAL CEILING TILES
P-2	SHERWIN WILLIAMS FLAT	P-2	SHERWIN WILLIAMS FLAT	ACOUSTICAL CEILING TILES
P-3	SHERWIN WILLIAMS SEMI-GLOSS	P-3	SHERWIN WILLIAMS SEMI-GLOSS	ACOUSTICAL CEILING TILES
PC-1	QUARRY TILE	PC-1	QUARRY TILE	ACOUSTICAL CEILING TILES
PC-2	POLISHED PORCELAIN TILE	PC-2	POLISHED PORCELAIN TILE	ACOUSTICAL CEILING TILES
PC-3	UNPOLISHED PORCELAIN TILE	PC-3	UNPOLISHED PORCELAIN TILE	ACOUSTICAL CEILING TILES
PC-4	ACCENT TILE	PC-4	ACCENT TILE	ACOUSTICAL CEILING TILES
FRP-1	FIBER REINFORCED PLASTIC	FRP-1	FIBER REINFORCED PLASTIC	ACOUSTICAL CEILING TILES
FRP-2	QUARRY TILE BASE	FRP-2	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-3	QUARRY TILE BASE	FRP-3	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-4	QUARRY TILE BASE	FRP-4	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-5	QUARRY TILE BASE	FRP-5	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-6	QUARRY TILE BASE	FRP-6	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-7	QUARRY TILE BASE	FRP-7	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-8	QUARRY TILE BASE	FRP-8	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-9	QUARRY TILE BASE	FRP-9	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-10	QUARRY TILE BASE	FRP-10	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-11	QUARRY TILE BASE	FRP-11	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-12	QUARRY TILE BASE	FRP-12	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-13	QUARRY TILE BASE	FRP-13	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-14	QUARRY TILE BASE	FRP-14	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-15	QUARRY TILE BASE	FRP-15	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-16	QUARRY TILE BASE	FRP-16	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-17	QUARRY TILE BASE	FRP-17	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-18	QUARRY TILE BASE	FRP-18	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-19	QUARRY TILE BASE	FRP-19	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-20	QUARRY TILE BASE	FRP-20	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-21	QUARRY TILE BASE	FRP-21	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-22	QUARRY TILE BASE	FRP-22	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-23	QUARRY TILE BASE	FRP-23	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-24	QUARRY TILE BASE	FRP-24	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-25	QUARRY TILE BASE	FRP-25	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-26	QUARRY TILE BASE	FRP-26	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-27	QUARRY TILE BASE	FRP-27	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-28	QUARRY TILE BASE	FRP-28	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-29	QUARRY TILE BASE	FRP-29	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-30	QUARRY TILE BASE	FRP-30	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-31	QUARRY TILE BASE	FRP-31	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-32	QUARRY TILE BASE	FRP-32	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-33	QUARRY TILE BASE	FRP-33	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-34	QUARRY TILE BASE	FRP-34	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-35	QUARRY TILE BASE	FRP-35	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-36	QUARRY TILE BASE	FRP-36	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-37	QUARRY TILE BASE	FRP-37	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-38	QUARRY TILE BASE	FRP-38	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-39	QUARRY TILE BASE	FRP-39	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-40	QUARRY TILE BASE	FRP-40	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-41	QUARRY TILE BASE	FRP-41	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-42	QUARRY TILE BASE	FRP-42	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-43	QUARRY TILE BASE	FRP-43	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-44	QUARRY TILE BASE	FRP-44	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-45	QUARRY TILE BASE	FRP-45	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-46	QUARRY TILE BASE	FRP-46	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-47	QUARRY TILE BASE	FRP-47	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-48	QUARRY TILE BASE	FRP-48	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-49	QUARRY TILE BASE	FRP-49	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-50	QUARRY TILE BASE	FRP-50	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-51	QUARRY TILE BASE	FRP-51	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-52	QUARRY TILE BASE	FRP-52	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-53	QUARRY TILE BASE	FRP-53	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-54	QUARRY TILE BASE	FRP-54	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-55	QUARRY TILE BASE	FRP-55	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-56	QUARRY TILE BASE	FRP-56	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-57	QUARRY TILE BASE	FRP-57	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-58	QUARRY TILE BASE	FRP-58	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-59	QUARRY TILE BASE	FRP-59	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-60	QUARRY TILE BASE	FRP-60	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-61	QUARRY TILE BASE	FRP-61	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-62	QUARRY TILE BASE	FRP-62	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-63	QUARRY TILE BASE	FRP-63	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-64	QUARRY TILE BASE	FRP-64	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-65	QUARRY TILE BASE	FRP-65	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-66	QUARRY TILE BASE	FRP-66	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-67	QUARRY TILE BASE	FRP-67	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-68	QUARRY TILE BASE	FRP-68	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-69	QUARRY TILE BASE	FRP-69	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-70	QUARRY TILE BASE	FRP-70	QUARRY TILE BASE	ACOUSTICAL CEILING TILES
FRP-71	QUARRY TILE BASE	FRP-71	QUARRY TILE BASE	ACOUSTICAL CEILING TILES